

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

S2 1 PN='JP 59045106'
? t2/7/1

2/7/1

DIALOG(R)File 350:Derwent WPIX
(c) 2003 Thomson Derwent. All rts. reserv.

003953115

WPI Acc No: 1984-098659/198416

Crystallised particulate polyester - based on alkylene terephthalate units, where only surfaces area is recrystallised

Patent Assignee: TEIJIN LTD (TEIJ)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
-----------	------	------	-------------	------	------	------

JP 59045106	A	19840313	JP 82154512	A	19820907	198416 B
-------------	---	----------	-------------	---	----------	----------

Priority Applications (No Type Date): JP 82154512 A 19820907

Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
-----------	------	-----	----	----------	--------------

JP 59045106	A		4		
-------------	---	--	---	--	--

Abstract (Basic): JP 59045106 A

The polyester is produced by treating it with heated steam at 110 deg. C or higher such that 300 is more than or equal to H is more than or equal to A/T (where H is treating time (sec.) with steam; T is temp. (deg. C); A is crystallisation degree of the polyester, i.e. a coefft. relating to the thickness t (mirons)) of crystallised surface layer, and is represented by the following equation; $A = \exp(at+b)$ (where a and b are 0.01-0.05, and 1.0-5.0 respectively)).

Crystallising the surface area of particulate polyester prevents the polyester particulate from adhering to one another on drying or solid-state polymerisation. Pref. thickness of the crystallised surface layer is 20 microns (more pref. 40 microns) or more, but long treating with the steam for thicker crystallisation generates increased water-content of polyester. Temp. of heated steam (satd. or super-heated one) is from 110 deg. C and usually up to 180 deg. C. Pref. treating time is 30 sec. or less.

O/O

Derwent Class: A23

International Patent Class (Additional): B29B-001/00; B29B-003/04